



# BRADYL BINS STORAGE LOCKER SPECIFICATIONS

## Standard Features:

### Wire Mesh Ceiling:

Thickness: 16 Gauge

Design: 2"x2" (center to center) square welded wire

### Doors

Swing Door: 26 gauge steel with reinforced solid-square tube X-bracing. 3" wide vertical stiles and 180 degree hinges. Factory installed slide latch that accepts padlock and over-lock.

### Hallway and Unit Divider Panels:

20" sections of corrugated 26 gauge steel.

### Corner Guard:

3"x3" white corner guard.

### Hardware:

Base channel, midspan, top channel, side angle, fasteners, teks screws, shot and pin Powder actuated fasteners.

### Finish:

Hallways: white

Interior partitions: galvanized metal

Doors: Select from available standard and upgraded colors

## Upgrade Options:

**Kick plate:** 12" aluminum diamond plated

**Diamond plate Corner Guard:** 3"x3" upgraded diamond plated corner guard

**Plug Latch and Master Keyed Cylinder Locks:** Plug latch factory installed on door. Locks furnished to be assigned by owner.

**Roll up Door:** Available in sizes up to 10'0" x 10'0". Slide latch that accepts padlock and over-lock is factory installed on the door. Upgraded latch/ Lock are available.

240-812-7012  
info@bradyl.com

[www.bradyl.com](http://www.bradyl.com)